



Product information

OK 2000 – DG purple # 562

OKULEN® OK 2000 - DG # 562 is a superior UHMW Polymer with a special wax type additive. It is designed for the conveying industry with enhanced gliding properties and no oil residue to attract dirt and grind. Noise reduction is another great benefit of this UHMW product. It can also be used as a normal UHMW PE liner.

Technical Values:

Properties	Unit	OK 2000-DG
abrasion index	%	70
coefficient of friction static	ASTM 1894	0,15
dynamic		0,09
density	g/cm ³	0,93
Shore-Hardness	D	62

Properties:

improved low coefficient of friction
excellent abrasion resistance
water repellent
complete resistance against chemical media
BfR + FDA approved
noise level reduction !

Color:

purple # 562

Application fields:

bottle & conveying industry (curves, profiles etc.)
Handling of bulk goods
Liner applications

The above data are based on the present knowledge and are given without guarantee.
Existing laws and conditions are to be respected by the user of our products.

TSE-OKULEN Americas, L.L.C.

sheet and finished products

4370 112th Terrace North, Clearwater, Florida 33762
www.TSE-OK.com E-mail: info@TSE-OK.com

A Joint Venture of TSE Industries, Inc., Clearwater, Florida (USA) and Ottensteiner Kunststoff GmbH & Co. KG (Germany).