



Product information

OK 2000 – H # 925

OKULEN® OK2000 – H # 925 is premier UHMW Polymer containing a unique antioxidant which protects the material from breaking apart at extreme temperatures. This material grade is used in high temp applications where normal UHMW fails. The enhanced material was designed to still operate effectively under lower load, with a temperature range peaking 300 °F.

Technical Values:

Properties	Unit	OK 2000-H
abrasion index	%	80
max. operation temperature	°F	300
density	g/cm ³	0,93

Properties:

long term operating temperature possible at
Peak range 300 °F (only at lower loads),
BfR + FDA approved
up to 10 x longer life time at higher temperatures
than any standard grade of UHMW PE

Color:

white colored # 925

Application fields:

Bakeries (bun racks)
Food industry
packing industry
Chemical Industry (laboratoruies)

The above data are based on the present knowledge and are given without guarantee.
Existing laws and conditions are to be respected by the user of our products.

TSE-OKULEN Americas, L.L.C.

sheet and finished products

4370 112th Terrace North, Clearwater, Florida 33762
www.TSE-OK.com E-mail: info@TSE-OK.com

A Joint Venture of TSE Industries, Inc., Clearwater,
Florida (USA) and Ottensteiner Kunststoff GmbH &
Co. KG (Germany).