



Product information

OK 2000 – Lub # 845

OKULEN® OK 2000 – L # 845 is a oil filled UHMW Polymer. This material was designed for the conveying (table top) industry. The enhanced lubricated oil filler helps on high speed chains or heavy dry run areas of the conveyor. Further, it helps reduce noise levels with its excellent gliding properties. This UHMW is known for its great impact strength and abrasion resistant surface quality. This material is FDA compliant for food applications.

Technical Values:

Properties	Unit	OK 2000-L
abrasion index	%	62
impact strength (15° double V-notch)	mJ/mm ²	> 80
density	g/cm ³	0,94
Shore hardness	D	62

Properties:

great gliding properties
water repellent
great noise reduction
lubricant stays on surface (oil)
no greasing required !

Color:

brown # 845

Application fields:

Conveyor industry
Fifth wheel application on trucks
Man lift truck extensions

The above data are based on the present knowledge and are given without guarantee.
Existing laws and conditions are to be respected by the user of our products.

TSE-OKULEN Americas, L.L.C.

sheet and finished products

4370 112th Terrace North, Clearwater, Florida 33762
www.TSE-OK.com E-mail: info@TSE-OK.com

A Joint Venture of TSE Industries, Inc., Clearwater,
Florida (USA) and Ottensteiner Kunststoff GmbH &
Co. KG, Germany