



Product information

OK 2000 – W # 703

OKULEN[®] OK 2000 – W # 703 is a wax filled UHMW polymer. The wax additive enhances the surface to increase (non-stick) sliding properties. This grade is used mostly in the food industry since it has been **FDA approved for food industry.**

Technical Values:

| Properties | Unit | OK 2000-W |
|-----------------------------------|-------------------|-----------|
| abrasion index | % | 80 |
| coefficient of friction static | ASTM 1894 | 0,16 |
| dynamic | | 0,10 |
| density | g/cm ³ | 0,93 |
| Shore-Hardness | D | 62 |

Properties:

noise reduction
good abrasion resistance
BfR + FDA approved
low driving power (cost effective)
great for dry runs

Color:

grey # 703

Application fields:

Conveyor industry
Food industry
Engineering applications

The above data are based on the present knowledge and are given without guarantee.
Existing laws and conditions are to be respected by the user of our products.

TSE-OKULEN Americas, L.L.C.

sheet and finished products

4370 112th Terrace North, Clearwater, Florida 33762
www.TSE-OK.com E-mail: info@TSE-OK.com

A Joint Venture of TSE Industries, Inc., Clearwater, Florida (USA) and Ottensteiner Kunststoff GmbH & Co. KG (Germany).